

Cable Clips

- · Forged Cable Clips, made in the USA.
- Used in conjunction with a thimble to form a loop at the termination of a cable.
- The efficiency rating of a properly prepared assembly is 80% of the catalog breaking strength of the wire rope.
- Clips are galvanized.
- · Meets Performance Requirements of Federal Specification FF-C-450, Type 1, Class 1.



Cable Clip 021-250C

Order Information

Number	Description	Weight
021-125C	1/8" (3.175 mm) Forged Cable Clip	0.1 lb. (0.05 kg)
021-187C	3/16" (4.76 mm) Forged Cable Clip	0.1 lb. (0.05 kg)
021-250C	1/4" (6.35 mm) Forged Cable Clip	0.2 lb. (0.09 kg)
021-312C	5/16" (7.9 mm) Forged Cable Clip	0.3 lb. (0.13 kg)
021-375C	3/8" (9.5 mm) Forged Cable Clip	0.5 lb. (0.23 kg)



Rope Clips

Clip Size Inches	Minimum Number of Clips	Amount of Rope to Turn Back in Inches	Torque in Ft. Lbs.
1/8"	2	3-1/4"	4.5
3/16"	2	3-3/4"	7.5
1/4"	2	4-3/4"	15
5/16"	2	5-1/4"	30
3/8"	2	6-1/2"	45
7/16"	2	7"	65
1/2"	3	11-1/2"	65
9/16"	3	12"	95
5/8"	3	12"	95
3/4"	4	18"	130
7/8"	4	19"	225
1"	5	26"	225
1-1/8"	6	34"	225
1-1/4"	7	44"	360
1-1/2"	8	54"	360







© 2016 Wenger Corporation USA/11-16/W



WENGER CORPORATION

JR CLANCY

Phone 800.4WENGER (493-6437) Worldwide 1.507.455.4100 | Fax 507.455.4258 Worldwide 1.507.774.8576 Parts & Service 800.887.7145 | Canada Office 800.268.0148 | Web wengercorp.com | 555 Park Drive, PO Box 448 | Owatonna | MN 55060-0448

GEARBOSS Phone 800.493.6437 | email gearboss@wengercorp.com | Web gearboss.com | 555 Park Drive, PO Box 448 | Owatonna | MN 55060-0448

Phone 800-836-1885 Worldwide 1.315.451.3440 | Fax 877.836.1885 Worldwide 1.315.451.1766 | Web jrclancy.com 7041 Interstate Island Road | Syracuse | NY 13209-9713