

SureGrip® Synthetic Rope

- The only theatrical rope with a wear indicator telling you when the rope needs replacing.
- The perfect replacement for manila and other ropes used backstage.
- Conventional, three-strand construction for a familiar feel and strong grip.
- Minimal stretch for easy use.
- Length does not change with temperature or humidity, so floor block readjustment is not necessary.
- Breaking strength for 3/4" (19 mm) SureGrip is 10,000 lbs. (4,535 kg), more than twice the strength of manila rope.
- Tracer tape with manufacturer's name, contact information and year manufactured.
- Sold in 600' (183 m) and 1200' (366 m) rolls.
- US Patent 7,461,500.



SureGrip Synthetic Rope

Order Information

Number	Description	RWL	Weight
028-750SGW6	3/4" (19 mm) Diameter SureGrip 600' Roll (183 m)	1050 lbs. (476 kg)	0.13 lb./ft. (0.19 kg/m)
028-750SGW12	3/4" (19 mm) Diameter SureGrip 1200' Roll (366 m)	1050 lbs. (476 kg)	0.13 lb./ft. (0.19 kg/m)
028-750SGB6	3/4" (19 mm) Diameter SureGrip, Black 600' Roll (183 m)	1050 lbs. (476 kg)	0.13 lb./ft. (0.19 kg/m)
028-750SGB12	3/4" (19 mm) Diameter SureGrip, Black 1200' Roll (366 m)	1050 lbs. (476 kg)	0.13 lb./ft. (0.19 kg/m)

RWL is based on manufacturer's 10:1 safety factor.



Design, Manufacture and Installation of Theatrical Equipment Worldwide

For unusual applications, J.R. Clancy can create custom equipment to match your facility's specific needs. Please contact us to discuss your project's requirements.



© 2016 Wenger Corporation
USA/11-16/W

